



氣體質量流量器 GAS MASS FLOWMETER

- RANGE: 0~1000 slpm
 - Response time: 2 seconds
 - Accuracy and Linearity : $\pm 1\% \sim 1.5\%$ F.S.
 - Repeatability: $\pm 2\%$ F.S.
 - Ambient and operation temperature: $-10 \sim 70^{\circ}\text{C}$
- PORTER MODEL 3261, MASS FLOW CONTROLLER**
- CLASS 1, DIV. 2 RATED
 - SP76 COMPLIANT
 - 2 POSITION DIRECT MOUNT
 - 24DC POWER
 - 4-20 mA I/O



液體質量流量器 Digital Liquid Mass Flow Controllers

- Response time: <1 second to within 5% of rate (up to 6 stored valve jump Voltages.
- Accuracy and Linearity : $\pm 1\%$.
- Repeatability: $< \pm 2\%$ of rate at any constant temperature with operation temperature range.
- Ambient and operation temperature: $-10 \sim 40^{\circ}\text{C}$.
- Maximum allowable pressure: 125 psig.
- Leak Integrity: 1×10^{-9} atm.cc/sec.He.
- Warm-up time: 20 minutes.
- External Electrical Connector: 9-pin D-connector
- Process connection: 1/8" male metal gasket face seal or 1/8" compression fitting.